

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 824 742 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
25.08.1999 Bulletin 1999/34

(51) Int Cl.⁶: **G07F 7/10**, G07F 19/00

(86) International application number:
PCT/EP96/02063

(21) Application number: **96916070.4**

(87) International publication number:
WO 96/36026 (14.11.1996 Gazette 1996/50)

(22) Date of filing: **10.05.1996**

(54) METHOD FOR EFFECTING AN ELECTRONIC PAYMENT TRANSACTION

VERFAHREN ZUM DURCHFÜHREN EINER ELEKTRONISCHEN ZAHLUNGSTRANSAKTION
PROCEDE POUR EFFECTUER UNE TRANSACTION DU TYPE PAIEMENT ELECTRONIQUE

(84) Designated Contracting States:
**AT BE CH DE DK ES FI FR GB GR IE IT LI LU NL
PT SE**

(73) Proprietor: **Koninklijke KPN N.V.**
9726 AE Groningen (NL)

(30) Priority: **11.05.1995 NL 1000341**
09.10.1995 NL 1001376

(72) Inventor: **PEDERSEN, Torben, P.**
DK-8230 Abyhøj (DK)

(43) Date of publication of application:
25.02.1998 Bulletin 1998/09

(56) References cited:
EP-A- 0 265 728 **EP-A- 0 459 781**
EP-A- 0 496 656 **EP-A- 0 507 669**

EP 0 824 742 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

[0001] The invention relates to a method for effecting, with an electronic payment means, a variable number of payments in one payment transaction. More in particular, the invention relates to a method for effecting a payment transaction with an electronic payment means and a payment station, comprising the issuing by the payment means to the payment station of at least a first payment value, payment values being representative for one or more payment units to be settled. Such a method is known, e.g. from European Patent Application EP-A-0,637,004. There are many types of payment transactions in which a variable number of payment units must be transferred. Thus, in a telephone booth, for a single conversation in most cases several units, corresponding with metering pulses (so-called "ticks"), should be debited against a payment card. These units are credited to the telephone set of the telephone booth. In the event of copiers, for a copying order a certain amount per page should be paid, with such amount being capable of being debited against a payment card. Within a single transaction (telephone conversation or copying order), therefore, a debiting of the payment means (i.e., the payment card) and a crediting of a payment station (telephone set or copier) must repeatedly take place.

[0002] In the event of modern, protected payment means, such as so-called "smart cards" or "chip cards", a protocol is applied to each debiting of the payment means (debit), in which the authenticity of the payment means and of the electronic money used is verified. An example of a verification schema using blind signatures is disclosed in European Patent Application EP-A-0,518,365. Another scheme to verify electronic money is disclosed in European Patent Application EP-A-0,507,669, where payment units are provided with random "sequence numbers". Verification of the electronic money is effected by checking received sequence numbers against a list of issued sequence numbers. However, this type of verification still allows the electronic money to be duplicated and to possibly be spent more than once.

[0003] A verification, however, for each payment unit (metering pulse or copying price per page) requires a certain processing time. In the event of, e.g., international telephone conversations, where the metering pulses (or ticks) follow each other rapidly, the processing of the payment units may give rise to problems and obstruct the execution of a protected payment.

[0004] In order to solve this problem, prior to the actual transaction several payment units might already be transferred from the payment means to the payment station. This has the drawback that restitution should take place in the event that not all payment units are used up. Payment afterwards, i.e., the transfer of payment

values from the payment means to the payment station following the transaction, has the drawback that the payment may be sabotaged by removing the payment means (i.e. the smart card) prematurely.

SUMMARY OF THE INVENTION

[0005] The object of the invention is to eliminate the above and other drawbacks of the prior art, and to provide a method which enables the effecting of a protected payment in a simple and rapid manner with a variable number of payment units, i.e. a number of payment units to be determined during the transaction.

[0006] Another object of the invention is to provide a method which allows a secure payment involving a minimal amount of processing time.

[0007] For this purpose, a method of the type referred to in the preamble is characterised in that the payment values are mutually related by a one-way function, in such a manner that the first payment value may be obtained from a further payment value by repeatedly applying the function. By applying a one-way function, i.e., a function of which the inverse cannot viably be determined, a very suitable check on the progress of the payment transaction may be obtained without the need to repeatedly execute a complicated and therefore time-consuming verification process.

[0008] After receiving a payment value, the payment station preferably checks, by applying the function, whether the payment value received is correct. This is possible since repeated application of the function produces the first payment value.

[0009] After receiving a payment value the payment station, by applying the function repeatedly, may additionally determine how many payment units the payment value received represents. Per payment transaction one or more payment values may be transferred, a (last) payment value possibly representing several (previous) payment values. The number of times the function must be applied to obtain the preceding or first payment value, is directly related to the number of payment values generated, but does not have to be equal to the number of issued and thus transferred payment values.

[0010] Together with at least the first payment value, authentication data is advantageously transferred from the payment means to the payment station. This authentication data, such as the identification code of the payment means and/or the user, may be contained in the first payment value or precede it.

[0011] In a further embodiment of the method according to the invention, the payment station, after receiving a payment value, transfers a debit value to the payment means. The debit values may be used, directly after having been received by the payment means, for debiting a balance, e.g., by lowering a counter reading present in the payment means. It is also possible, however, that after having been received by the payment means the debit values are collected and, at the end of the payment

transaction, are used for debiting a balance. In the latter case, the method may progress more rapidly.

[0012] In yet a further embodiment of the method according to the invention, together with the debit value a count value is transferred from the payment station to the payment means, which count value represents the number of payment units to be debited. The count value may be one, but may also be greater than one, so that several payment units are debited simultaneously. The count value may furthermore have been determined in advance, or be variable. Preferably, the count value is related to the number of times the one-way function is applied, e.g., to obtain the preceding or the first payment value.

[0013] In a yet another embodiment of the method in accordance with the invention the issued payment values are used as proof in a settlement process to be carried out later. In this case, with the issued payment value (s) a payment is laid down while the settlement of payment can take place at another time. Such a settlement can for example result in a summary invoice.

[0014] The method according to the invention enables to adjust as needed, during the transaction, the number of payment values and thus the number of payment units to be settled.

EXEMPLARY EMBODIMENTS

[0015] The invention will be explained in greater detail below with reference to the Figures.

- Fig. 1 shows a smart card as may be used in the method of the present invention.
- Fig. 2 schematically shows the integrated circuit of the smart card of Fig. 1.
- Fig. 3 schematically shows a preferred embodiment of the method according to the invention.
- Fig. 4 schematically shows successive function values of a one-way function.

[0016] The smart card or IC card 1 shown by way of example in Fig. 1 comprises a substrate 2, in which an integrated circuit is embedded. The integrated circuit is provided with contacts 3 for contacting a card reader or the like. It should be noted that the present invention can also be applied in the case of so-called contactless smart cards.

[0017] The integrated circuit 10 shown schematically and by way of example in Fig. 2 comprises a processor 11, a memory 12 and an input/output circuit 13. The memory may comprise a volatile (RAM) memory part for temporarily storing data and a non-volatile (ROM) memory part for permanently or semi-permanently storing data. The latter part is preferably an EEPROM type memory. The data stored in the non-volatile part may contain both programming data (instructions, programs) and payment data, i.e. data relating to monetary trans-

actions. It will be understood that a separate memory (not shown) may be provided to store the instruction set of the processor 11. The input-output circuit 13 may communicate with external devices via contacts (not shown in Fig. 2), such as the contacts 3 shown in Fig. 1. The integrated circuit 10 may be contained in the card 1 of Fig. 1.

[0018] In Fig. 3, there is schematically shown, by way of example, an embodiment of the method according to the invention. A payment means (paying party) is referred to by I, and a payment station or terminal (receiving party) is referred to by II. Between the payment means I and the payment station II, during a payment transaction an exchange of data takes place. It will be understood that the payment means (card) I may correspond with the smart card 1 shown in Fig. 1.

[0019] At the time to, there may take place an exchange of initialisation values I (or Init). This exchange, which inter alia may relate to the identity of the payment station and/or the payment means, the type of transaction and the like, is not essential to the present invention.

[0020] At the time t_1 , the payment means (card) I sends an authentication value A and a first payment value β_M to the payment station (terminal) II. The payment value β_M may, like the debit value R, be contained in the authentication value A or may be determined by the authentication value A, e.g. when A is constituted by a digital signature on β_M , R and other transaction data. The payment value β_M need therefore not constitute a separate value.

[0021] After authentication, the payment station provides access to the desired service or the desired product and saves the authentication value A and the payment value β_M as proof of payment, e.g. vis-à-vis a banking institution. Alternatively, β_M or one or more possible subsequent values β_{M-1} , β_{M-2} , ..., may serve as proof to later collect money from a consumer (compare so-called credit cards). In his context it should be noted that the settlement of the transaction is, in principle, independent of the transaction proper and may be carried out at another time and another place.

[0022] At the time t_2 , the payment station II sends a debit value R to the payment means, possibly accompanied by a count value N. The count value N may have a previously determined fixed value, e.g., one. In this case, the transfer of the count value N may be dispensed with, or may be effected only once (time t_2).

[0023] On the basis of the debit value R, one or more payment units are debited against a balance on the card, e.g., by lowering a counter reading (see also e.g. EP-A-0,637,004). This number of payment units to be debited may be predetermined, or may be referred to by the count value N. Also the debit value R may be predetermined, because of which R is redundant and may be dispensed with. Instead of R_1 , or R and N, a generic debit signal may be transferred. The debiting may take place directly or shortly after the time t_2 , or may be postponed till the end of the transaction. In the latter case,

the payment means will be constructed in such a manner that this debiting takes place even if the transaction is prematurely interrupted.

[0024] As a reaction to the receipt of the debit value R, or as a reaction to the receipt of an interim request (not shown in Fig. 3) from the payment station, at the time t_3 the payment means I sends a further payment value, β_{M-1} , to the payment station II. In the payment station II, A and β_{M-1} are now saved as proof of payment. In addition, $F(\beta_{M-1})$ is calculated; in other words, β_{M-1} is subjected to the function F. If the result of this operation indeed produces β_M , not only has a check on the authenticity of β_{M-1} been effected, but the number of payment values is also determined: the total number of payment values is equal to the number of operations required to obtain β_M plus one. It follows that in the event of receiving a payment value β_{M-x} , the value of x may be determined by applying the function F x times. Thus, the count value N may be adjusted on the basis of the value of x found. This will be explained later with reference to Fig. 4.

[0025] At the time t_4 , a further debit value R is transferred from the payment station II to the payment means I, possibly together with a count value N. The payment means carries out similar operations as at the time t_2 .

[0026] After the time t_4 , further similar steps may be carried out, or the transaction may be terminated. The transaction will be terminated anyway after the last payment value β_0 has been transferred. Possibly, an acknowledgement of the termination of the transaction may be transferred from the payment station II to the payment means I. This is not further indicated in Fig. 3.

[0027] As is explained above, the number of payment units to be debited is variable and may depend on the duration of the transaction, inter alia.

[0028] In summary, the method according to the invention, at any rate if use is made of debit values, comprises the following steps:

1. The payment means sends a value β to the payment station.
2. The payment station sends a debit value to the payment means.
3. The payment means sends a value of (β') derived from β , determined with the help of the one-way function, to the payment station.
4. The payment station checks whether the received value β' is indeed a value derived from β .
5. If the transaction has not been terminated, β is replaced by its derived value β' , and the process continues at step 2.

The derived value referred to here is always the value β' for which:

$F(\beta') = \beta$, i.e. the value "preceding" β .

[0029] It should be noted that the method described above may also be terminated after step 2, that is in case only one payment unit, such as a telephone tick (meter-

ing pulse), is to be transferred.

[0030] The payment values β referred to above may each represent one payment unit, such as a telephone tick, currency unit or calculation unit. It is also possible, however, that each payment value represents several payment units, or that different payment values represent different numbers of payment units. This may be recorded in the authentication value A. The first payment value may e.g. represent a base rate of several (e.g., two or three) payment units, while further payment values always represent one payment unit. In this manner, a differentiation may be made between, e.g., the set-up costs and the duration costs of a telephone connection. The payment values consist of numbers which are transferred in the form of electrical, optical or acoustical signals.

[0031] The so-called one-way function F per se is simple to calculate, but the inverse (F^{-1}) cannot viably be determined. This is understood to mean that in practice it is extremely unlikely that a value β_{M-1} may be determined from a value β_M . Such a one-way function, known per se from cryptography, may be constructed, e.g., by involution modulo a certain number, in which that specific number may be a so-called "Blum integer", i.e. a product of two large prime numbers in a special form. A so-called "hash" function may also be applied.

[0032] In Fig. 4, the application of the one-way function is further illustrated with reference to an example. In this example, M is equal to 5 (see also Fig. 3), so that the first payment value is β_5 . In practice, M will have a much greater value, e.g., 255.

[0033] A value β_i ($i=0\dots 5$) may simply be calculated from the value β_{i-1} by applying the one-way function F: $F(\beta_{i-1})=\beta_i$. Conversely, it is very difficult to determine the inverse of F, so that in practice it is not viable to determine the value β_{i-1} from β_i . In the method according to the invention, this provides a form of guarantee: the payment station is able to check whether the value β_i is correct and what is the (relative) value thereof by applying the function F several times. Conversely, the payment station itself is not able to calculate the next payment value, which represents a greater number of payment units.

[0034] As may be seen from Fig. 4, the value β_5 may be obtained from β_2 by applying the function F three times. If the payment station first receives β_5 and then β_2 , it may therefore be determined that β_2 is the fourth payment value (relative to β_5) and, e.g., represents four payment units (i.e. the units associated with β_5 plus β_4 plus β_3 plus β_2). In response thereto, e.g., a count value N-4 may be transferred to the payment means in order to debit four payment units at once. If no value β_5 results after the function F has been applied at most M (in this case 5) times to β_2 , it may be concluded that the most recently received value (i.e. β_2) is invalid, as the values β_5 and β_2 are apparently not related by F.

[0035] The possession of a valid β_2 therefore demonstrates that the receiver (the payment station) is entitled

to payment units corresponding to four payment values: β_2 through β_5 . These may be four payment units but, e. g., also four times C payment units, where C is a conversion factor.

[0036] As explained above, the use of a one-way function provides a simple and rapid method for effecting payments with a variable number of payment units. This may not only be advantageous in the case of telephony, but for example also in the case of vending machines, taximeters, and other devices where the amount to be settled can be dependent on the time duration.

[0037] The payment values issued need not be settled, for example by means of debit values, during or immediately afterwards a transaction with a payment means, but may be used as proof in a settlement process to be carried out at a later time. In this case a payment is laid down with the issued payment means, while the settlement of the payment can take place at a later time (incontestable charging). Such a settlement may for example result in a summary invoice with several transactions being settled in one settlement process. Using payment values as proof for settlements afterwards, can for example be used with mobile telephone and video distribution services (video-on-demand).

[0038] The invention may be applied with or without so-called electronic "cheques" comprising an electronic "signature" (e. g., a cryptographic operation with a specific key on certain data) of the bank and/or the user.

[0039] It will be understood by those skilled in the art that the invention is not limited to the embodiments shown, and that many modifications and amendments are possible without departing from the scope of the invention as defined in the appended claims.

Claims

1. Method for effecting a payment transaction with an electronic payment means (1, I) and a payment station (II), comprising the issuing by the payment means to the payment station of at least a first payment value (β_M), payment values being representative for one or more payment units to be settled, characterised in that each subsequent payment value (β_{M-1} , β_{M-2} , ...) is related to the first payment value (β_M) by a one-way function (F) in such a manner that the first payment value (β_M) may be obtained from a further payment value (β_{M-x}) by repeatedly applying the function (F).
2. Method according to claim 1, wherein the payment station (II), after receipt of a payment value (β_I), checks by applying the function (F) whether the payment value received is correct.
3. Method according to claim 1 or 2, wherein the payment station (II), after receipt of a payment value (β_I), determines by applying the function (F) how

many payment units the payment value received represents.

4. Method according to any of the preceding claims, wherein authentication data (A) is transferred together with at least the first payment value (β_M) from the payment means (I) to the payment station (II).
5. Method according to any of the preceding claims, wherein the payment station (II), after receipt of a payment value (β_I), transfers a debit value (R) to the payment means.
6. Method according to claim 5, wherein debit values (R) are used, directly after receipt by the payment means (I), for debiting a balance.
7. Method according to claim 5, wherein debit values (R), after receipt by the payment means (I), are collected and, at the end of the payment transaction, are used for debiting a balance.
8. Method according to any of the claims 5 up to and including 7, wherein a count value (N) is transferred, together with the debit value (R), from the payment station (II) to the payment means (I), which count value (N) represents the number of payment units to be debited.
9. Method according to claim 8, wherein the count value (N) is related to the number of times the one-way function (F) has been applied.
10. Method according to claim 8, wherein the count value (N) amounts to one.
11. Method according to any of the claims 1 up to and including 4, wherein the payment values (β_I) issued are used as proof in a settlement process to be carried out later.
12. Payment means (1, I) provided with an integrated circuit (10), such as a so-called smart card, the integrated circuit (10) being arranged for effecting a payment transaction with a payment station (II) by issuing to the payment station (II) at least a first payment value (β_M), payment values being representative for one or more payment units to be settled, characterised in that each subsequent payment value (β_{M-1} , β_{M-2} , ...) is related to the first payment value (β_M) by a one-way function (F) in such a manner that the first payment value (β_M) may be obtained from a further payment value (β_{M-x}) by repeatedly applying the function (F).
13. Payment means according to claim 12, further arranged for transferring, together with at least the first payment value (β_M), authentication data (A) to

the payment station (II).

14. Payment means according to claim 12 or 13, further arranged for receiving and collecting debit and/or count values (R, N) from the payment station (II) and for debiting a balance at the end of the payment transaction with an amount represented by said values (R, N).

Patentansprüche

1. Verfahren zum Durchführen einer Zahlungstransaktion mit einem elektronischen Zahlungsmittel (1, I) und mit einer Zahlungsstation (II), mit der Ausgabe von mindestens einem ersten Zahlungswert (β_M) von dem Zahlungsmittel an die Zahlungsstation, wobei Zahlungswerte repräsentativ für eine oder mehrere zu bezahlende Zahlungseinheiten sind, **dadurch gekennzeichnet**, dass jeder nachfolgende Zahlungswert (β_{M-1} , β_{M-2}) mit dem ersten Zahlungswert durch eine Ein-Weg-Funktion (F) in solch einer Weise verbunden ist, dass der erste Zahlungswert (β_M) aus einem weiteren Zahlungswert (β_{M-x}) durch wiederholtes Anwenden der Funktion (F) erhalten werden kann.
2. Verfahren nach Anspruch 1, dadurch gekennzeichnet, dass die Zahlungsstation (II) nach Empfang eines Zahlungswertes (β_i) durch Anwenden der Funktion (F) überprüft, ob der empfangene Zahlungswert richtig ist.
3. Verfahren nach Anspruch 1 oder Anspruch 2, dadurch gekennzeichnet, dass die Zahlungsstation (II) nach Empfang eines Zahlungswertes (β_i) durch Anwenden der Funktion (F) feststellt, wie viele Zahlungseinheiten der empfangene Zahlungswert darstellt.
4. Verfahren nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, dass Authentifizierungsdaten (A) zusammen mit mindestens dem ersten Zahlungswert (β_M) von dem Zahlungsmittel (I) an die Zahlungsstation (II) übertragen werden.
5. Verfahren nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, dass die Zahlungsstation (II) nach Empfang eines Zahlungswertes (β_i) einen Belastungswert (R) an das Zahlungsmittel übermittelt.
6. Verfahren nach Anspruch 5, dadurch gekennzeichnet, dass Belastungswerte (R) direkt nach dem Empfang durch das Zahlungsmittel (I) zur Belastung eines Guthabens eingesetzt werden.
7. Verfahren nach Anspruch 5, dadurch gekennzeichnet,

net, dass Belastungswerte (R) nach dem Empfang durch das Zahlungsmittel (I) gesammelt werden und bei der Beendigung der Zahlungstransaktion zur Belastung eines Guthabens eingesetzt werden.

8. Verfahren nach einem der Ansprüche 5 bis 7, dadurch gekennzeichnet, dass zusammen mit dem Belastungswert (R) ein Zählwert (N) von der Zahlungsstation (II) an das Zahlungsmittel (I) übertragen wird, wobei der Zählwert (N) die Anzahl der zu belastenden Zahlungseinheiten darstellt.
9. Verfahren nach Anspruch 8, dadurch gekennzeichnet, dass der Zählwert (N) zur Anzahl der Anwendungen der Ein-Weg-Funktion (F) in Bezug steht.
10. Verfahren nach Anspruch 8, dadurch gekennzeichnet, dass der Zählwert (N) Eins ist.
11. Verfahren nach einem der Ansprüche 1 bis 4, dadurch gekennzeichnet, dass die ausgegebenen Zahlungswerte (β_i) als Beweis für ein nachfolgend auszuführendes Bezahlungsverfahren eingesetzt werden.
12. Zahlungsmittel (1, I) mit einem integrierten Schaltkreis (10), wie eine sogenannte Smartcard, wobei der integrierte Schaltkreis (10) derart ausgestaltet ist, um eine Zahlungstransaktion mit einer Zahlungsstation (II) durchzuführen, indem mindestens ein erster Zahlungswert (β_M) an die Zahlungsstation ausgegeben wird, wobei Zahlungswerte repräsentativ für eine oder mehrere zu bezahlende Zahlungseinheiten sind, **dadurch gekennzeichnet**, dass jeder nachfolgende Zahlungswert (β_{M-1} , β_{M-2} , ...) mit dem ersten Zahlungswert (β_M) durch eine Ein-Weg-Funktion (F) in solch einer Weise verbunden ist, dass der erste Zahlungswert (β_M) aus einem weiteren Zahlungswert (β_{M-x}) durch wiederholtes Anwenden der Funktion (F) erhalten werden kann.
13. Zahlungsmittel nach Anspruch 12, dadurch gekennzeichnet, dass es so ausgestaltet ist, um Authentifizierungsdaten (A) zusammen mit mindestens dem ersten Zahlungswert (β_M) an die Zahlungsstation (II) zu übertragen.
14. Zahlungsmittel nach Anspruch 12 oder 13, dadurch gekennzeichnet, dass es weiterhin ausgestaltet ist, um Belastungswerte und/oder Zählwerte (R, N) von der Zahlungsstation zu übermitteln und um ein Guthaben am Ende der Zahlungstransaktion mit der durch die genannten Werte (R, N) repräsentierten Geldwerte zu belasten.

Revendications

1. Procédé d'exécution d'une transaction de paiement avec un moyen électronique de paiement (1, I) à une station de paiement (II), comprenant la délivrance par le moyen de paiement à la station de paiement d'au moins une première valeur de paiement (β_M), les valeurs de paiement étant représentatives d'une ou plusieurs unités de paiement à régler, caractérisé en ce que chaque valeur ultérieure de paiement (β_{M-1} , β_{M-2} , ...) est liée à la première valeur de paiement (β_M) par une fonction univoque (F) de manière que la première valeur de paiement (β_M) puisse être obtenue à partir d'une valeur supplémentaire de paiement (β_{M-x}) par application répétée de la fonction (F).
2. Procédé selon la revendication 1, dans lequel la station de paiement (II), après réception d'une valeur de paiement (β_i), vérifie, par application de la fonction (F), si la valeur de paiement reçue est convenable.
3. Procédé selon la revendication 1 ou 2, dans lequel la station de paiement (II), après réception d'une valeur de paiement (β_i), détermine, par application de la fonction (F), combien d'unités de paiement représente la valeur de paiement reçue.
4. Procédé selon l'une quelconque des revendications précédentes, dans lequel des données d'authentification (A) sont transférées avec au moins une première valeur de paiement (β_M) à partir du moyen de paiement (I) à la station de paiement (II).
5. Procédé selon l'une quelconque des revendications précédentes, dans lequel la station de paiement (II), après réception d'une valeur de paiement (β_i), transfère une valeur de débit (R) au moyen de paiement.
6. Procédé selon la revendication 5, dans lequel les valeurs de débit (A) sont utilisées directement après réception par le moyen de paiement (I) pour le débit d'un solde.
7. Procédé selon la revendication 5, dans lequel les valeurs de débit (R), après réception par le moyen de paiement (I), sont collectées et, à la fin de la transaction de paiement, sont utilisées pour le débit d'un solde.
8. Procédé selon l'une quelconque des revendications 5 à 7 incluse, dans lequel une valeur de comptage (N) est transférée avec la valeur de débit (R) depuis la station de paiement (II) au moyen de paiement (I), cette valeur de comptage (N) représentant le nombre d'unités de paiement à débiter.
9. Procédé selon la revendication 8, dans lequel la valeur de comptage (N) est liée au nombre de fois où la fonction univoque (F) a été appliquée.
10. Procédé selon la revendication 8, dans lequel la valeur de comptage (N) est égale à 1.
11. Procédé selon l'une quelconque des revendications 1 à 4 incluse, dans lequel les valeurs de paiement (β_i) qui sont délivrées sont utilisées comme preuve d'une opération de règlement exécutée ultérieurement.
12. Moyen de paiement (1, I) muni d'un circuit intégré (10), tel qu'une carte électronique, le circuit intégré (10) étant destiné à effectuer une transaction de paiement avec une station de paiement (II) par délivrance à la station de paiement (II) d'au moins une première valeur de paiement (β_M), les valeurs de paiement étant représentatives d'une ou plusieurs unités de paiement à régler, caractérisé en ce que chaque valeur ultérieure de paiement (β_{M-1} , β_{M-2} , ...) est liée à la première valeur de paiement (β_M) par une fonction univoque (F) de manière que la première valeur de paiement (β_M) puisse être obtenue à partir d'une valeur supplémentaire de paiement (β_{M-x}) par application répétée de la fonction (F).
13. Moyen de paiement selon la revendication 12, destiné en outre à transférer, avec au moins la première valeur de paiement (β_M), des données d'authentification (A) à la station de paiement (II).
14. Moyen de paiement selon la revendication 12 ou 13, destiné en outre à recevoir et collecter des valeurs de débit et/ou de comptage (R, N) provenant de la station de paiement (II) et à débiter un solde à la fin de la transaction de paiement avec une somme représentée par les valeurs R, N.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.